

# FIFTYFOURMS

## Rules for the operation of furniture and other products

**The regulations contain a list of mandatory requirements for the operation of the products. Compliance with these rules is a prerequisite for the validity of the warranty.**

### Joinery products:

1. Joinery products are designed for use in rooms with a constant relative humidity of 30-50% and an air temperature within 15-28 degrees C above zero.
2. Repair work (plastering, whitewashing, etc.) should be completed in the room where the products are to be installed, as the humidity should be 30-50%. Excessive dryness and humidity are equally harmful to natural wood and veneer products.
3. During storage and use, carpentry products should be protected from mechanical damage, moisture, aggressive substances, direct sunlight, fire and sudden changes in temperature and humidity of the surrounding air.
4. Furniture should not be subjected to unreasonable loads, which should be evenly distributed and not exceed the permissible norm.
5. Proper care of all surfaces during use is essential. Dust should be removed from the polished or lacquered surface of the furniture using a dry, soft cloth (flannel, mike). It is recommended that the polished or lacquered surfaces of the joinery be wiped with refreshing compositions specially designed for wax-based furniture. Do not use baking soda, powders or pastes not intended for the maintenance of products.

Sudden changes in temperature and humidity in the room are not allowed (not more than 5% per hour).

It is forbidden to pour water or other liquids on the products or to wipe them with a wet cloth (this can leave streaks or white stains that spoil the appearance of the products). Any liquid accidentally spilt on the surface should be removed immediately with a dry cloth.

Protect the surfaces of painted products from liquids, especially those that dissolve paint (alcohol, acetone, petrol). Do not place hot objects on the surface of products without a thermal underlay.

For products that are fastened with bolts, screws, nuts, bolts, screws should be retightened when connections are loosened.

6. Products should not be installed near damp and cold walls or heat sources. Products should only be installed or repositioned by lifting the product by the plinth. If the doors do not close due to uneven floors when installing or moving the products, a spacer must be placed under the plinth. For safety reasons, cabinets over 1 metre in height should always be fixed to the wall.

### **Upholstered furniture:**

When using upholstered furniture, it is important to remember that it should only be used for its intended purpose and that all permissible loads should be taken into account:

Sofas	Distributed load 160 - 220 kg
Armrest	40 kg
Armchair	120 kg
Chair	90 kg
Pouf	90 kg
Single bed	120 kg
Double bed	240 kg

1. Failure to observe the permissible loads may result in deformation of the frame and panels.
2. The recommended air temperature is +18 to +28 degrees C, with a relative humidity of 30 to 80%. Do not place the furniture near radiators. Avoid exposure to liquids, prolonged exposure to direct sunlight and sudden temperature changes.
3. Move the product by lifting it slightly on the main frame.
4. Professional cleaning is recommended for upholstery care. Domestic washing of upholstery is prohibited, as is drying with hair dryers, irons and other household appliances. A steamer can be used to smooth creases.